



طلب شراء أجهزة ضرورية لإدارة هندسة الإرسال الإذاعي

(1) جهاز توزيع الأصوات:



FR6822+F Frame 2RU no ba



This Device shall be contained:

- HARRIS 6800 (FR6822+) SP785.
- HARRIS 6800 (FR6822+) AES 6800+B.



طلب شراء أجهزة ضرورية لإدارة هندسة الإرسال الإذاعي

(2) جهاز موزع الأصوات:



D-Splitter E1SS-1080

(3) جهاز تشفير الأصوات:

Harmonic – Multiplexer



This Device shall be contained:

- FAN like mentions in BOQ.



طلب شراء أجهزة ضرورية لإدارة هندسة الإرسال الإذاعي

5. مجفف الهواء Dehydrator



PART #	XT300-92026
MANUFACTURER	Commscope-Andrew
GENRE	Pressurization

GENERAL SPECIFICATIONS

DEW POINT	Better than -40 °C (-40 °F) at 95% RH at +40 °C (+104 °F)
PORT TYPE	3/8 in PE tube
RACK TYPE	EIA 19 in
MOUNT TYPE	Shelf Wall
VOLTAGE TYPE	ac
DEHYDRATOR TYPE	Programmable Automatic Membrane
FLOW RATE, NOMINAL	0.30 SCFM 8.50 SLPM
VOLUME CAPACITY, MAXIMUM	80.0 ft ³
VOLUME CAPACITY, MINIMUM	2.0 ft ³

ELECTRICAL SPECIFICATIONS

VOLTAGE	230 Vac ±10%
POWER CORD	Europe power cord with stripped leads
POWER PHASE	Single
POWER FREQUENCY	50 Hz
ALARM CONTACT RATING	Form C dry contacts, 2 amps at 30 Vdc
SUGGESTED CIRCUIT BREAKER SIZE	15 A



طلب شراء أجهزة ضرورية لإدارة هندسة الإرسال الإذاعي
جدول الكميات

No.	Description	(Model)No	Qty.	Price KD	Total price
1	POWER SUPPLY	HARRIS 6800(FR6822+) SP785	1		
2	AES 6800+B	HARRIS 6800(FR6822+) AES 6800+B	2		
3	OPTIMOD 5500 DIGITAL	(ORBAN)	1		
4	D – SPLITER	E1SS-1080	2		
5	FAN	8P8:822531 – 001	2		
6	FAN	GM1204PQV 1 – 8A DC12V 2.8W 4*4*2.7 CM	4		
7	LNB	KU – BAND PLL FREQ RANGE : 10.7 – 11.8 GHZ LO 9.75 GHZ LO STABILLTY +/- 250 KHZ 12-24 VDC	1		
8	Dehydrator	XT300-92026	1		
9	POWER SUPPLY	FPS1000 Series	2		
TOTAL PRICE:					